

HighSpeed USB3.0 LTO Tape Drive

LT90H/80H2/70H2/60H USB/SAS

World's Only USB Connection LTO High Speed USB 3.0 LTO Tape Drive









Function

- High speed data transfer at maximum 300MB/sec
- Plug and play with USB3.0 interface
- Hybrid model with USB interface and SAS interface is also available
- Large amounts of LTO capacity
- Support Mac, Windows, Linux

lodel	LT90H Half-Height	
tive/Compression)	18TB/45TB	
Native	300 MB/sec	
Compression	300 MB/sec	
Native	300 MB/sec	
Compression	750 MB/sec	
	ive/Compression) Native Compression Native	

Features

- With USB plug and play connection, enable maintenance without stopping the server
- USB cable clamp prevents unexpected cable disconnection
- Support various use
 - Backup & transfer large amounts of data
 - Archive data in Broadcast/Video/Surveillance camera/Medical
 - Countermeasure for Ransomware by managing data off-line
- UNITEX LTFS3000 software is included
 - No special knowledge and skills are required for data storage to LTO tape
 - Data can be copied to LTO tape by drag & drop





USB cable clamp

Comparison with conventional model (Performance improvement)

Writing time of LTO-9 (18TB) 1pc



LT90H USB finally achieves the same speed with data transfer rate of 300MB/sec with SAS connection.

25% increase in transfer speed over the previous model (240MB/sec) enables easy and stress-free backup/archiving in any environment, including laptop PCs that cannot be equipped with SAS interface.

High Speed LTSeries

Example of using LT series

Archive in Broadcast/Video industry



Archive at Factory/Production site



- Manage ever-increasing data assets easily with connecting to a laptop PC
- Pass and receive large amounts of data efficiently by LTO tape media
- Enable data sharing among different OS's with LTFS support



- Store CAD data such as drawings efficiently
- Ideal for long term storage of inspection data, inspection result, and trace data
- Record X-ray sensor data of foreign articles contamination and metal sensor data



Specification

High Speed USB 3.0 LTO tape drive

Model	LT90H USB	LT80H2 USB	LT70H2 USB	LT60H USB	
Drive Type	LTO Ultrium9	LTO Ultrium8	LTO Ultrium7	LTO Ultrium6	
Interface	USB3.0				
Capacity	18.0TB (Native) / 45.0TB (2.5:1 Compression)	12.0TB (Native) / 30.0TB (2.5:1 Compression)	6.0TB (Native) / 15.0TB (2.5:1 Compression)	2.5TB (Native) / 6.25TB (2.5:1 Compression)	
Native data transfer (Max)	USB3.0: 300MB/sec	USB3.0: 300MB/sec	USB3.0: 300MB/sec	USB3.0:160MB/sec	
OS support	Mac / Windows / Linux				
Dimensions (mm)	213(W) x 370(D) x 58(H) mm				
Power Supply	AC100~240V ±10%, 50/60Hz				
Power Consumption	55VA	65VA			
Weight	4.5kg				
Operating Environment	Temperature 10'C~40'C Humidity 20%~80% (No condensation)				
Kit Contents	LTO Tape Drive / USB3.0 cable / Cleaning Cartridge / User Guide (English) / UNITEX LTFS3000 software (English)				

High Speed USB 3.0/SAS LTO tape drive

Model	LT90H USB/SAS	LT80H2 USB/SAS	LT70H2 USB/SAS	LT60H USB/SAS	
Drive Type	LTO Ultrium9	LTO Ultrium8	LTO Ultrium7	LTO Ultrium6	
Interface	USB 3.0 / 12Gbps SAS (SFF-8644)	USB 3.0 / 6Gbps SAS (SFF-8088)			
Capacity	18.0TB (Native) / 45.0TB (2.5:1 Compression)	12.0TB (Native) / 30.0TB (2.5:1 Compression)	6.0TB (Native) / 15.0TB (2.5:1 Compression)	2.5TB (Native) / 6.25TB (2.5:1 Compression)	
Native data transfer (Max)	USB3.0:300MB/sec SAS:300MB/sec	USB3.0:300MB/sec SAS:300MB/sec	USB3.0:300MB/sec SAS:300MB/sec	USB3.0:160MB/sec SAS:160MB/sec	
OS support	Mac / Windows / Linux				
Dimensions (mm)	213(W) x 370(D) x 58(H) mm				
Power Supply	AC100~240V ±10%, 50/60Hz				
Power Consumption	55VA	65VA			
Weight	4.5kg				
Operating Environment	Temperature 10°C~40°C Humidity 20%~80% (No condensation)				
Kit Contents	LTO Tape Drive / USB3.0 cable / Cleaning Cartridge / User Guide (English) / UNITEX LTFS3000 software (English)				





You can manage all the data offline as well.



^{*} Company names, product names, software names are either trade marks or registered trademarks of respective companies. * Specifications are subject to change without notice

DOC-L9HE1-AD 22110001

